



**MATERIALS AND FINISH**

SHELL : STEEL MATERIAL, TIN FINISHED  
 INSULATOR : PBT GF, UL 94V-0 , BLACK COLOR  
 SIGNAL CONTACT : COPPER ALLOY, GOLD FLASH  
 METAL WATERTIGHT FRAME : PBT GF, UL 94V-0, BLACK COLOR  
 O-RING : SILICONE  
 EPOXY SEALANT : EPOXY

**ELECTRICAL CHARACTERISTICS**

SIGNAL CONTACT CURRENT RATING : 5.0 AMPS  
 SIGNAL CONTACT RESISTANCE : 10 mΩ MAX.  
 DIELECTRIC WITHSTANDING VOLTAGE : 1000 V FOR 1 MINUTE  
 INSULATION RESISTANCE : 5GΩ MIN.  
 TEMPERATURE RATING : -55°C ~ +105°C  
 DEGREE OF PROTECTION : IP67 ACCORDING TO IEC60529

**Allconnectors**

www.allconnectors.eu | info@allconnectors.eu  
 Tel. +49 (0)711 / 358 110 20 | Fax +49 (0)711 / 358 110 25

REV	CONTENTS		DATE		DWG NO:					
	DRAWN	HAO			WDS0-25FTB0					
	CHKD	HAO			CUSTOMER --					
	APPD	JORDAN			SCALE	2:1	SIZE	A4	REV	001
	MATERIAL	--	SCALE	2:1	SIZE	A4	REV	001		
	FINISH	--	UNITS	mm	DATE	2008/08/28				

TOLERANCES	
X.	±0.40
.X	±0.30
.XX	±0.20
.XXX	±0.10
X°.	±0.30
.X°	±0.20
.XX°	±0.10